

Material Safety Data Sheet

Product Name ENOC VULCAN 660X , SAE 20W- 50

Product Code 200021

1. IDENTIFICATION OF SUBSTANCE/PREPARATION AND COMPANY

Product Name ENOC VULCAN 660X
Viscosity 20 W- 50
Appli ca tion DIESEL ENGINE OIL
Company Identificat ion ENOC **International Sales L LC**
EN OC Complex, **Sheikh Rashid** Road,
P.O. Box: 6442, Dubai

Telephone 971 4 3374400

Fax 971 4 3134616

2. COMPOSITION/INFORMATION ON INGREDIENTS

COMPOSITION: Blended with mineral base oil SN 150 & SN 500 CAS 64742-65-0 at 78.4 % with additive concentrate at 21.6 % .

Chemical nature: Petroleum derived severely refined mineral base product in which the polycyclic aromatic hydrocarbons (PCA or PAH) content measured by IP 346 is above 3%.

Substance contributing to hazards: None to our knowledge in normal use.

Impurities contributing to hazards: None to our knowledge.

3. HAZARDS IDENTIFICATION

According to experience the product is considered to be harmless to health if handled correctly.

4. FIRST AID MEASURES

General Information	Remove contaminated clothing immediately, to be disposed of or washed before reuse.
Inhalation	If inhaled, provide fresh air, warmth, rest and medical advice if necessary.
Skin Contact	Clean areas of skin affected with soap and copious water. If necessary seek medical advice.
Eye Contact	In case of contact with eyes, rinse immediately with plenty of water until irritation subsides.
Ingestion	Allow the patient to vomit on his own accord. Give copious water to drink and seek medical help if necessary.

Material Safety Data Sheet

Product Name ENOC VULCAN 660X , SAE 20W- 50

Product Code 200021

5. FIRE FIGHTING MEASURES

Extinguishing Media	To suit local surroundings (eg water spray, carbon dioxide foam, chemical powder).
Special Exposure Hazard	Decomposition products released in a fire should be considered as probably harmful if inhaled (see Stability and Reactivity section).
Protective Equipment	Wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Methods for Cleaning Up	Take up with absorbent material, eg sand, sawdust and dispose of as prescribed. Do not allow to get into waste water or waterways; if this occurs, inform the relevant authority at once.
-------------------------	--

7. HANDLING & STORAGE

Advice on Safe Handling	Handle in accordance with good hygiene and safety practice. Avoid temperatures >65
Advice on Protection against Fire & Explosion	N/A
Storage Conditions	Ensure adequate ventilation of storage area. Keep container tightly closed, cool (< 85) and dry.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Controls	Monitoring of the workplace should be considered in accordance with EH40 (or equivalent) Controls. LTEL (8 hour TWA): 5 mg/m ³ (EH40, 1998) STEL (15 min): 10 mg/m ³ (EH40, 1998) OES data for oil mist, mineral In addition the Reciprocal Calculation Procedure (RCP) for hydrocarbons should be considered (EH40, 1998)
Engineering Controls	Ensure adequate ventilation of working area eg Local Exhaust Ventilation.
Personal Protection	Observe normal safety standards for handling chemicals. Avoid inhalation of vapour. Avoid contact with skin and eyes. Wear personal protective equipment appropriate for the task eg gloves, safety goggles, respirators (eg if ventilation is inadequate), appropriate overalls.

Material Safety Data Sheet

Product Name ENOC VULCAN 660X , SAE 20W- 50

Product Code 200021

9. PHYSICAL & CHEMICAL PROPERTIES

Specific Gravity	Approx. 0.89 (ASTM D1298 at 15°C)
Auto-ignition Temperature	N/A
Vapour Pressure	N/A
Toxicity	N/A
Relative Density	N/A
Boiling Point	From 350°C
Pour Point	- 27°C (ASTM D97)
Flammability	N/A
Flash Point	Open cup: approx. 238 °C
Viscosity	At 100°C: approx. 21.29 mm ² /s (ASTM D445)
Viscosity	At 40°C: approx. 190.1mm ² /s
Apparent Viscosity	At 15°C: approx. 3300 mPa.s
KOH content	11 mg/g (TBN ASTM 2 896)
pH	N/A
Solubility	In water: negligible
Description	Light pale liquid with petroleum like odour.

10. STABILITY & REACTIVITY

Stability	N/A
Thermal Decomposition	Not determined
Conditions To Avoid	N/A
Material To Avoid	N/A
Hazardous Reactions	The product does not undergo hazardous polymerisation.
Hazardous Decomposition Products	Oxides of carbon, aldehydes, ketones, and of hydrogen sulphide plus combustion products of nitrogen and sulphur.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity	No acute toxicological data are available. LD ₅₀ rat (oral): N/A LD ₅₀ rat (i.v.): N/A
Dermal Compatibility	N/A
Mucous Membrane Compatibility	N/A

ENOC LUBRICANTS

Version No. 1
Revision Date: New
Authorisation Date: 26/01/2012

Material Safety Data Sheet

Product Name ENOC VULCAN 660X, SAE 20W- 50

Product Code 200021

12.ECOLOGICAL INFORMATION

Ecotoxicology	Ecotoxicological data are not available.
Further Ecological Information	N/A
Further Information	The product must not enter ground or waste water. If this occurs, inform the local authority at once. Calcium content: approx. 0.229% by mass (atomic absorption)

13. DISPOSAL CONSIDERATIONS

Advice on Disposal	In accordance with national and local authority regulations, eg special waste or incineration after consultation with the operators.
Contaminated Packaging	Treat emptied containers in the same way as the product, or if possible wash out thoroughly and recycle.

14. TRANSPORT INFORMATION

Transportation Measures	Not determined
-------------------------	----------------

15.REGULATORY INFORMATION

Classification & Labelling	Product is not classified in accordance with the Chemical (Hazard Information and Packaging for Supply Regulations (CHIP 97)).
Risk Phrases	N/A
Safety Phrases	N/A

ENOC LUBRICANTS

Version No. 1
Revision Date: New
Authorisation Date: 26/01/2012

Material Safety Data Sheet

Product Name ENOC VULCAN 660X, SAE 20W- 50

Product Code 200021

16. OTHER INFORMATION

Date of Issue 26/01/2012

General Summary

N/A

This information is based on our present state of knowledge and is intended to describe our products from the point of view of the safety requirements. It should not be construed as guaranteeing specific properties.