

زيوت محركات فائقة الأداء

PREMIUM MOTOR OILS

ENOC Lubricants

ENOC Lubricants - a specialized lubricants division of EISL - has developed its own quality range of branded automotive and industrial lubricants. These are marketed, via a distribution network, throughout more than 30 countries across the Middle East, Asia, CIS and Africa.

The division's philosophy is to maintain the highest quality standards from manufacturing through to packaging and distribution. Its products meet the latest international specification standards such as API and ACEA, and are approved to OEM specifications. They are supplied on-time and in hi-tech packaging. Technical staff provide expert advice and a laboratory service to test oils and investigate equipment conditions.

Viscosity - SAE	Technical Specifications
-----------------	--------------------------

MOTOR OILS

Protec Green	5W-30, 5W-40 Fully Synthetic, Low SAP Technology	ACEA C3/A5/B5, API SM/CF, MB 229.51, BMW Long life-04 VW 502.00/505.00/505.01, PORSCHE Cars
Protec X-TREME	5W-40 Fully Synthetic	API SM/CF, ACEA A3/B4, MB 229.3, BMW Long life-98 VW 502.00/505.00, PORSCHE Cars
Protec X-TREME ENERGY	5W-30 Fully Synthetic Energy conserving	ILSAC GF4, API SM, FORD WSS M2C 913-B/929-A/930-A
Protec Ultra	10W-40 Semi Synthetic	API SL/CF, ACEA A3/B4, MB 229.1, VW 500.00/505.00
Protec Premium	10W-30, 10W-40, 15W-40, 20W-50	API SL/CF, ACEA A2/B2
Protec Super SL	20W-50	API SL/CF, ACEA A2/B2
Protec Premium SJ	10W-40	API SJ/CD, ACEA A2/B2
Protec Super SG	10W-30, 10W-40, 15W-40, 20W-50	API SG/CD
Protec Super SF	20W-50	API SF/CC
Protec Max	10W-30, 10W-40 15W-40,20W-50	API SF/CC
Protec HD SF	40, 50	API SF/CC
Protec HD SE	40, 50	API SE/CC

DIESEL ENGINE OILS

Vulcan 770 SLD	10W-40 Fully-Synthetic	API C14, ACEA E7/E4, MB 228.5, Volvo VDS-3, Renault RLD2/RXD, MAN M 3277, MTU 3.0
Vulcan Green	10W-40 Fully-Synthetic Low SAP Technology	ACEA, E7/E6/E4 MAN 3477 (Low SAP) MB 228.51/228.5, Volvo VDS-3, Renault RXD, MTU 3.1/3.0
Vulcan 880X	15W-40	API CJ4/SM, ACEA E7, CAT ECF-3 MB 228.3, MAN M 3275, Cummins 20081, Volvo VDS-4, Renault RDL-3, EMA DHD-1, DDC 93k218, MACK EO-O
Vulcan 770X	15W-40	API C14/SL, ACEA E5/E7, MB 228.3, Volvo VDS-3, MAN M 3275, MTU 2.0, Renault RLD-2, MACK EO-M Plus, Cummins 20076/20077/20078
Vulcan 700X	15W-40	API CH4/SJ, ACEA E3, MB 228.3, Volvo VDS-2, MAN M 3275, CAT TO-2, MACK EO-M
Vulcan 660X	15W-40, 20W-50	API CG4/SJ, ACEA E2/B2/A2, MB 228.1, Volvo VDS, MAN 271, Allison C4, CAT TO-2
Vulcan 550X	15W-40, 20W-50	API CF4/SJ, ACEA E2/B2/A2, MB 228.1, Volvo VDS, MAN 271, Allison C4
Vulcan 330X	15W-40, 20W-50	API CF/SF, CAT TO-2
Vulcan 330	10W, 30, 40, 50	API CF, CAT TO-2
Vulcan 3320 Special	40, TBN 20 ZINC FREE	API CF/CF2, LMOA Generation 4, GE 61435C, GM EMD
Vulcan 330C	40, TBN 20	API CF/SF
Vulcan Super Duty	15W-40, 20W-50 40, 50	API CD/SE
Vulcan HD	40, 50	API CC/SC
Vulcan DD	40	API CF2



Viscosity - SAE	Technical Specifications
-----------------	--------------------------

AGRICULTURAL TRACTOR OILS

Tractor STO	15W-30, 15W-40, 20W-40 Multi Purpose Tractor Oil	API CD, API GL4, Allison C4, Ford M2C 159B, JD J20A, Massey M1135, HYD ISO 68/100
Tractor UTF	ISO 68 Universal Tractor Oil	API GL4, Allison C4, Ford M2C 134D, JD J20C/D, Massey M1135, M1141, Cat TO2, Case International J/C 145, V1150

AUTOMOTIVE GEAR OILS

Zenon Ultra LSD	80W-90, Limited Slip	API GL-5, ZF TE-ML 05C, 12C
Zenon Ultra Plus	80W-90, 85W-140	API GL-5, MIL-L-2105D, Mack GO-G
Zenon Ultra	90, 140	API GL-5, MIL-L-2105D, Mack GO-G
Zenon Premium Plus	80W-90, 85W-140, 80W-85, 80W	API GL-4, MIL-L-2105, ZF TE-ML 02, Man 341 Type Z-1
Zenon Premium	90, 140	API GL-4, MIL-L-2105
Zenon Super	90, 140	API GL-3
Zenon	90, 140	API GL-1

AUTOMOTIVE TRANSMISSION FLUIDS

Active Premium		Dexron®IIIH/Mercon®, (obsolete) Allison C4
Active Super		Dexron®IID (obsolete), VOITH G 607, CAT TO 2, ZF TE-ML 09B, 11A, 14C
Active CTF	10W, 30, 50	CAT TO-4, Allison C-4, API CF (Level), ZF TEML 01, 03, EATON Transmissions, KOMATSU KES 07-868.1
Active VTS	DEXRON VI	GM DEXRON® VI

TWO-STROKE ENGINE OILS

Protec 2T Super Outboard		NMMA TC-W3®
Protec 2T Premium LS		JASO FC (Low Smoke)
Protec 2T Super		API TB, JASO FB
Protec 2T		API TA

FOUR-STROKE MOTORCYCLE ENGINE OILS

Protec 4T Premium	20W-50	JASO MA, API SL
Protec 4T Super	10W-30, 15W-40, 20W-50	JASO MA, API SG (Level)
Protec 4T Max	10W-40, 20W-50, 40	JASO MA, API SF
Protec 4T	40	JASO MB, API SE

SPECIALITY OILS

Hydraulic HD 10W	10W	API CD CAT TO2
EN-Flush	ISO 32	Mineral Oil
Ultra Brake Fluid		Brake Fluid DOT 4
Super Brake Fluid		Brake Fluid DOT 3
EN-COOL Extra Long Life Coolant	EC 33 & EC 50 (HOAT)	BS 6580, ASTM 4985/6210 service life 200000 km
EN-COOL Long Life Coolant	EC (HOAT) 33 & 50	BS 6580-BS 5117, ASTM 4656/6210,service life 100000 km
EN-COOL Engine Coolant	EC 30 & EC 50	BS 6580 (1992), ASTM 3306/4985/5345/4656/SAE J 1941
Axis H	ISO 32, 46, 68, 100, 150	DIN 51524/2, Denison HF-O

GREASES

Verron LX Grease	NLGI 2, 3	Lithium complex, Wheel Brg and Chassis grease
Verron EP Grease	NLGI No 1, 2, 3	Lithium base, Wheel Brg and Chassis
Verron MP Grease	NLGI No 2, 3	Lithium base, centralized systems, pre-packed bearings
Verron Moly EP Grease	NLGI No 2	Lithium base with 3% MoS ₂
Cerion EP Grease	NLGI No 2, 3	Calcium base, MoS ₂ Centralized grease systems

Note: Please refer to www.enoclubricants.com for the complete product range.