



# ENOC PROTEC 2T SUPER OUTBOARD

**PROTEC 2T SUPER OUTBOARD** is the latest generation of two-stroke engine lubricant for high performance outboard engines. It has been formulated with special base stocks that provide a low ash lubricant to help support the protection of lakes and oceans. **PROTEC 2T SUPER OUTBOARD** exceeds the latest NMMA TC-W3<sup>®</sup> certified oil specification requirements for high performance two-stroke engines.

## APPLICATIONS

- ◆ Modern low emission outboard two-stroke engines.
- ◆ All makes of 2-cycle outboard motor engines.
- ◆ Oil-injected engines.
- ◆ Oil-gasoline premix engines up to gasoline to oil ratios 100:1

## PERFORMANCE STANDARDS

**PROTEC 2T SUPER OUTBOARD** meets and exceeds the following OEM and International specifications:  
NMMA (National Marine Manufacturers Association) TC-W, TC-W II<sup>®</sup> TC-W3<sup>®</sup> *certified*

***Always follow equipment manufacturer's recommendation for required lubricant performance levels.***

## BENEFITS

**PROTEC 2T SUPER OUTBOARD provides:**

- ◆ Reduced engine deposits.
- ◆ Improved environmental exhaust pollution protection.
- ◆ Reduced engine wear.
- ◆ Minimised tendency for pre-ignition.
- ◆ Trouble free operation.
- ◆ Long engine service life.
- ◆ Lower maintenance costs.

**PROTEC 2T SUPER OUTBOARD** mixes readily with gasoline as a "premix" and is equally suitable for metered lube injection systems. The best advise on mixing is to:

- Fill the tank half with gasoline
- Pour in the correct amount of oil
- Add the remainder of gasoline
- Follow the manufacturers' recommendations for mixing oil to gasoline ratios.

Technical Data*	
<b>SAE Grade (J1536)</b>	<b>F/M3</b>
Kinematic Viscosity	
mm <sup>2</sup> /s @ 100°C	6.62
mm <sup>2</sup> /s @ 40°C	38.72
Flash Point, PMCC, °C	84
Pour Point, °C	-21
Sulphated Ash	0.589
Product Code	220006

\*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

## HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.