



ENOC ACTIVE VTS

PRODUCT DESCRIPTION

ENOC ACTIVE VTS is a synthetic automatic transmission fluid designed specifically for use in Continuous Variable Transmission (CVTs). It can also be used in conventional 5 and 6 speed automatic transmissions. **ACTIVE VTS** has extended drain interval capabilities due to its superior oxidation stability, deposit control and resistance to viscosity shear loss. It has stable static and dynamic coefficients of friction, prevents noise generation and has smooth lock-up of the transmission clutches.

APPLICATIONS

- ◆ CVT transmissions
- ◆ Allison transmissions
- ◆ 5 and 6 speed conventional automatic transmissions

PERFORMANCE STANDARDS

ACTIVE VTS meets and exceeds the following OEM and International specifications:

GM	Dexron VI	Honda	CVT fluid
Allison	TES 295 fluid	Nissan	CVT fluid
Ford	Mercon V		
JASO	M315-02		

Always follow equipment manufacturer's recommendation for required lubricant performance levels and oil drain intervals.

BENEFITS

ACTIVE VTS provides:

- ◆ Suitable for a range of CVT transmissions
- ◆ Excellent shear stability
- ◆ Extended long drain intervals
- ◆ Protection against copper corrosion
- ◆ Smooth gearshift changes
- ◆ Very good low temperature fluidity

Technical Data*	
Colour	Red
Viscosity mm ² /s @ 100°C	7
Viscosity mm ² /s @ 40°C	36.96
Viscosity cPs @ -40°C	13,000 max
Pour Point, °C	-54
Flash Point, °C	226
Viscosity Index	152
Product Code	221007

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.