

ENOC VULCAN SVI 70

PRODUCT DESCRIPTION

VULCAN SVI 70 oil is developed for the lubrication of old heavy goods vehicles used in general transport diesel engines. It is designed specifically for use in naturally aspirated diesel engines. Formulated for moderate to severe service depending on the diesel fuel sulphur level and oil change frequency.

APPLICATIONS

- ◆ Heavy goods vehicles in general transport.
- ◆ Suitable for old diesel engines.

PERFORMANCE STANDARDS

VULCAN SVI 70 meets the following International specifications:

API CF
 ACEA E3- 96

Always follow equipment manufacturer's recommendations for required lubricant performance levels and oil drain intervals.

BENEFITS

VULCAN SVI 70 provides:

- ◆ An economical product with good all round performance.
- ◆ Suitability for use on old model diesel engines.
- ◆ Good resistance to corrosion

Technical Data*	
Density kg/ m3	0.8944
Kinematic Viscosity mm ² /s @ 40 ⁰ C	370.1
mm ² /s @100 ⁰ C	30.24
Viscosity Index	114
Flash Point, COC, ⁰ C	274
Pour Point, ⁰ C	-15
BN No. ASTM D2896	11.02
Product code	200050

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.