



# ENOC HYDRAULIC HD

## PRODUCT DESCRIPTION

**ENOC HYDRAULIC HD** is a SAE 10W & SAE 30 engine oil used in hydraulic applications where mobile equipment manufacturers recommend SAE 10W & SAE 30 engine oil. It has been developed to provide special antiwear protection to minimise mobile equipment pump wear also includes rust and corrosion inhibitors to protect the hydraulic system working surfaces.

## APPLICATIONS

- ◆ Mobile earth moving equipment, scrapers, diggers, shovels
- ◆ Heavy duty off-road dump trucks
- ◆ Commercial vehicle hydraulic tipping gear
- ◆ Agriculture tractors and other farm equipment

## PERFORMANCE STANDARDS

**ENOC HYDRAULIC HD** meets and exceeds the following OEM and International specifications:

API CD  
Caterpillar TO-2

***Always follow equipment manufacturer's recommendations for required lubricant performance levels and oil drain intervals.***

## BENEFITS

**ENOC HYDRAULIC HD provides:**

- ◆ Wide application of mobile equipment
- ◆ Low pump wear due to special anti-wear additive technology
- ◆ Minimum breakdown of the hydraulic equipment
- ◆ Cost effective performance
- ◆ Suitability for harsh climate conditions

Technical Data*		
SAE Grade	10W	30
Kinematic Viscosity mm <sup>2</sup> /s @ 40°C	31.1	97.93
mm <sup>2</sup> /s @ 100°C	5.32	11.12
Viscosity Index	103	98
Flash Point, COC, °C	218	242
Pour Point, °C	-18	-15
Zinc, ppm (minimum)		900
BN No. ASTM D2896	5	5
Product Code	200019	200048

\*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

## HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.