



VULCAN HD

PRODUCT DESCRIPTION

VULCAN HD is a range of monograde diesel engine oils developed for older model light pick-ups and heavy duty commercial vehicles that operate on standard oil drain intervals. The resulting oils meet or exceed the requirements of API Service Classifications CC and U.S. Military Specification MIL-L-2104B.

APPLICATIONS

- ◆ A wide range of diesel engine light trucks
- ◆ Older model gasoline engine cars and pick-ups
- ◆ Road transport, commercial vehicles operating on standard oil drain periods
- ◆ Mobile light duty generator sets

PERFORMANCE STANDARDS

VULCAN HD meets and exceeds the following International specifications

API	CC, SC
CCMC	D1
U.S. Military	MIL-L-2104B

Always follow equipment manufacturer's recommendations for required lubricant performance levels and oil drain intervals.

BENEFITS

VULCAN HD provides:

- ◆ New formulation technology for improved engine cleanliness
- ◆ Rationalisation in mixed vehicle fleet operations
- ◆ Economical lubrication which assists in lower vehicle maintenance costs
- ◆ Cost effectiveness for small fleet and owner, driver operators

Technical Data*		
SAE Grade	40	50
Kinematic Viscosity mm ² /s @ 40 ^o C	154.2	248.3
mm ² /s @ 100 ^o C	14.96	21.1
Viscosity Index	97	100
Flash Point, COC, ^o C	264	264
Pour Point, ^o C	-15	-15
BN No. ASTM D2896	4.0	4.0
Product code	200002	200003

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.