



ENOC PROTEC SUPER SL

PRODUCT DESCRIPTION

ENOC PROTEC SUPER SL is a modern high technology based gasoline engine oil suitable for modern passenger cars operating in harsh climatic conditions as found in the Middle East and Asia. Developed to provide maximum protection for the latest generation of passenger cars and high performance vehicles. It is available in SAE 20W-50 viscosity grade and exceeds the latest API service classification SL. Compatible for all cars running on lead free gasoline and catalytic converters.

APPLICATIONS

- ◆ Latest model passenger cars
- ◆ High performance normally aspirated and turbocharged gasoline engines
- ◆ Four stroke motorcycle engines where motor oils are recommended
- ◆ Japanese and American manufactured cars
- ◆ Light commercial vehicles

PERFORMANCE STANDARDS

PROTEC SUPER SL meets and exceeds the following International specifications:

API SL/CF, SH
ACEA A2-98/2, B2-98/2

Always follow equipment manufacturer's recommendations for required lubricant performance level and oil drain intervals

BENEFITS

PROTEC SUPER SL provides:

- ◆ The highest level of engine protection for all model years
- ◆ Extended engine life
- ◆ Superior resistance to oil thickening
- ◆ Excellent protection against wear
- ◆ Low oil consumption and engine deposits
- ◆ Easy all year round starting

Technical Data*	
SAE Grade	20W-50
Kinematic Viscosity	
mm ² /s @ 40 ^o C	187
mm ² /s @ 100 ^o C	20.6
Viscosity Index	129
Flash Point, COC, ^o C	236
Pour Point, ^o C	-30
Product Code	210008

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.