

ENOC CERION EP GREASE

PRODUCT DESCRIPTION

ENOC CERION EP are high quality Calcium greases suitable for a range of applications. It is available in NLGI 2 and 3 consistencies. They are formulated for use in automotive equipment and general lubrication and where water contamination is present. The high quality base oils used in the manufacture of these greases have good resistance to oxidation and have low pour point.

APPLICATIONS

- Automotive water pump bearings, steering joints and other chassis plain and anti-friction bearing applications
- ◆ Chassis-lubrication and centralised grease systems
- ◆ General purpose grease lubrication for mobile equipment

RECOMMENDATIONS

CERION EP minimises wear under high bearing load conditions and resists water wash-out, especially where equipment is constantly working under damp or wet conditions. It is also effective in the protection against rust and corrosion. Where vehicles are lubricated by centralised grease systems, **CERION EP** has good pumpability characteristics.

Always follow equipment manufacturer's recommendation for required grease performance and re-lubrication periods.

BENEFITS

CERION EP provides:

- ◆ Resistance to water washout
- ◆ Excellent adhesion properties
- ◆ Good pumpability
- ◆ Good mechanical stability
- ◆ Multifunctional use

Technical Data*		
NLGI Grade	2	3
Colour	Dark Brown	Dark Brown
Soap Thickener	Calcium	Calcium
Dropping point, °C	95	112
Penetration, Worked 25°C	280	195
Oil Viscosity mm ² /s @40°C	120	120
Oil Viscosity mm ² /s @100°C	17	17
Operating temperature range, °C	≤ 60	≤ 60
Tackiness and EP agents	Present	Present
Texture	Smooth	Smooth

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.