



ENOC EN-FLUSH OIL

PRODUCT DESCRIPTION

ENOC EN-FLUSH OIL is manufactured from high quality light viscosity paraffinic mineral oil, designed for the efficient EN-FLUSH of automotive equipment to remove residues prior to refilling with new engine lubricant.

APPLICATIONS:

EN-FLUSH OIL has been developed for the use in the flushing of automotive gasoline and diesel engines. It cleans the crankcase, cylinder walls, pistons and rings for maximum efficiency, protection and performance. This is done while the engine is in idling so that there is less stress on the engine while the cleaning action occurs.

RECOMMENDATIONS:

EN-FLUSH OIL Once the EN-FLUSH oil has been filled into the engine system it should be circulated for only a short time under light or no load conditions. At the end of the EN-FLUSH period, make sure the oil is drained while it is still hot.

KEY BENEFITS:

- Improve oil flow for better performance.
- Reduce risk of clogged oil galleries & ports.

Technical Data*	
Kinematic Viscosity mm ² /s @ 40°C	32
mm ² /s @100°C	5.0
Flash Point, PMCC, °C	210
Viscosity Index	95
Pour Point, °C	-12
Product Code	210006

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.