

# ENOC PROTEC 4T SUPER POWER SM

## PRODUCT DESCRIPTION

**ENOC PROTEC 4T SUPER POWER SM** is extra high performance motor oil designed to provide high level of protection in motor cycle gasoline engines. It is formulated from hydrotreated mineral oils and a superior additive package to provide outstanding overall engine cleanliness and protection against wear at high temperatures and under severe conditions. Excellent fluidity at low temperatures which ensures starting in cold weather and low volatility contributes to low consumption. It is available in SAE 20W-50 viscosity grade and exceeds the latest API service classification SM and JASO MA2. Well suited for 4 stroke motor cycle engine , clutch and gear (ECG)

## APPLICATIONS

- ◆ All modern 4 stroke motor cycle gasoline engine.

## PERFORMANCE STANDARDS

**PROTEC SUPER PLUS** meets and exceeds the following International specifications:

API        SM/CF  
 JASO      MA2

***Always follow equipment manufacturer's recommendations for required lubricant performance level and oil drain intervals***

## BENEFITS

**PROTEC SUPER Plus provides:**

- ◆ The highest level of engine protection
- ◆ Extended engine life
- ◆ Superior resistance to oil thickening
- ◆ Excellent protection against wear
- ◆ Low oil consumption and engine deposits
- ◆ Easy all year round starting

SAE Grade	20W-50
Kinematic Viscosity mm <sup>2</sup> /s @ 40°C	188.9
mm <sup>2</sup> /s @ 100°C	20.94
Viscosity Index	131
Flash Point, COC, °C	235
Pour Point, °C	-27
Product code	220028

\*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

## HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.