



# ENOC VERRON LCX 2 GREASE

## PRODUCT DESCRIPTION

**ENOC VERRON LCX** is a mixed soap base, lithium and calcium grease with molybdenum disulphide and EP chemistry to provide excellent performance in arduous automotive applications. It has outstanding resistance to shock loading in plain bearings, 5<sup>th</sup> wheel and other chassis applications, in addition, it has good adhesion to metal surfaces, water resistance, oxidation and rust inhibitor properties

## APPLICATIONS

- ◆ Heavy loaded automotive bearings
- ◆ General construction and quarrying equipment bearings subjected to heavy or shock loading
- ◆ Chassis components subjected to severe loads and 5<sup>th</sup> wheel applications
- ◆ General mobile equipment
- ◆ Effective temperature range -10°C to 120°C

***Always follow equipment manufacturer's recommendation for required grease performance and re-lubrication periods.***

## BENEFITS

### VERRON LCX 2 provides:

- ◆ Excellent extreme pressure properties
- ◆ Good resistance to wet operating conditions
- ◆ Outstanding mechanical stability
- ◆ Excellent anti-wear performance
- ◆ Wide temperature operations

Technical Data*	
NLGI Grade	2
Colour	Anthracite
Dropping point, °C	180
Penetration, Worked @ 25°C	280
Base oil Viscosity mm <sup>2</sup> /s @ 40°C	210
Four ball weld load in Kgs	370
Operating temperature range °C	-10 to 120

\*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

### HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.