



ENOC SUPER BRAKE FLUID

PRODUCT DESCRIPTION

ENOC SUPER BRAKE FLUID is a high quality synthetic brake and clutch fluid conforming to the DOT3 specification and based on polyglycol type fluid that is a general standard used in worldwide automotive brake equipment.

APPLICATIONS

- ◆ Suitable for passenger cars, trucks and buses that require synthetic brake fluid.

PERFORMANCE STANDARDS

SUPER BRAKE FLUID meets and exceeds the following International specifications:

FMVSS 116 for DOT 3

SAE J-1703

ISO 4925 and NFR 12640.

Always follow equipment manufacturer's recommendation for required brake fluid performance level.

BENEFITS

SUPER BRAKE FLUID provides:

- ◆ High wet boiling point
- ◆ Excellent low-temperature stability
- ◆ Good temperature viscosity performance
- ◆ Excellent corrosion protection
- ◆ Compatibility with different rubber seals
- ◆ Excellent thermal stability

CAUTIONARY NOTE:

SUPER BRAKE FLUID should not be used where a mineral type fluid is specified (e.g. Citroen).

COMPATIBILITY

SUPER BRAKE FLUID is compatible with other DOT 3, SAE 1703 fluids and may be added as make-up fluid. It can be used throughout mixed fleets thereby avoiding the need to order stock and use a special fluid for different brake systems.

Technical Data*	
Boiling Point, °C	205
Wet Boiling Point, °C	140
Viscosity	
mm ² /s @ -40°C	1250
mm ² /s @ 100°C	2.0
pH Value	10.3
Product Code	223001

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.