



# ENOC ZENON ULTRA LSD

## PRODUCT DESCRIPTION

**ENOC ZENON ULTRA LSD** fluid has been developed specifically for Limited Slip differentials providing superior quality multigrade gear performance. The formulation contains special friction properties that reduce transmission noise and extended life with smooth operation. Recommended for self-blocking axles equipped with limited slip differentials requiring SAE 80W-90

## APPLICATIONS

- ◆ Limited Slip Differentials for cars, 4X4 vehicles, light trucks under extreme operating conditions
- ◆ Suitable for use with self-blocking axle rear wheel differentials

## PERFORMANCE STANDARDS

**ZENON ULTRA LSD** meets and exceeds the following OEM and International specifications:

API GL-5  
ZF TE-ML 05C, 12C

***Always follow equipment manufacturer's recommendations for the required lubricant performance level and oil drain interval.***

## BENEFITS

### **ZENON ULTRA LSD provides:**

- ◆ Shudder free operation due to special lubricant with modified friction characteristics
- ◆ Special Extreme pressure anti-wear performance provides long gear life
- ◆ Eliminates stick-slip conditions in difficult 4X4 off-road operations and high performance cars with Limited Slip differentials.

Technical Data*		
SAE Grade	80W-90	85W-140
Kinematic Viscosity		
mm <sup>2</sup> /s @ 40 <sup>0</sup> C	164	403.10
mm <sup>2</sup> /s @ 100 <sup>0</sup> C	16	28.44
Viscosity Index	100	97
Flash Point COC <sup>0</sup> C	218	218
Pour Point, <sup>0</sup> C	-27	-15
Product Code	222011	222018

\*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

### **HEALTH AND SAFETY, ENVIRONMENT**

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.