



ENOC ZENON

PRODUCT DESCRIPTION

ENOC ZENON has been developed for use in mechanical transmissions that require an oil meeting API GL-1. It is formulated from high quality, paraffinic type base oils. **ENOC Zenon** is not suitable for extreme pressure gear oil applications.

APPLICATIONS

- ◆ Certain manual transmissions
- ◆ Steering boxes where API GL-1 is required
- ◆ Suitable for certain manual gear transmissions and spiral-bevel axles
- ◆ Lightly loaded worm drive gears

PERFORMANCE STANDARDS

ZENON meets and exceeds the following International specification

API GL-1

Always follow equipment manufacturers recommendations for required lubricant performance levels and oil drain intervals.

BENEFITS

ZENON provides:

- ◆ Smooth gear operation with mild anti-wear performance
- ◆ Good rust and corrosion resistance
- ◆ Resistance to foaming
- ◆ Good transmission life through resistance to oxidation

Technical Data*		
SAE Grade	90	140
Kinematic Viscosity mm ² /s @ 40 ^o C	168	360
mm ² /s @ 100 ^o C	17.5	31
Viscosity Index	96	95
Pour Point, ^o C	-9	-6
Product Code	222012	222013

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.